# **QUELINE RESCUE TOOLS ENT.**

### **FIREFIGHTING SAFETY TOOLS**

### EMERGENCY ESCAPE MASK (DISPOSABLE)

- Silver color, made of aluminum fabric with good fire resistance and light reflection property. It can supply at least 40 minutes of breathable air once in a fire.
- The water absorption of dryer (active carbon as carrier) in filter, It can protect Hopcalite when in use. Hopcalite material in filter, It can filter carbon monoxide(CO) and other gases.



### Brand: XHZLC 40

### **EMERGENCY ESCAPE MASK**

Silicone sealing gaskets, suitable for long tome to wear Polycarbonate lenses, anti-Scratching Wide scope of application Buckle type Connection Unique central adapter design Breathing valve is not easy to contaminate 3M patent cold flow exhalation valve Dual Tank full face Mask Low respiratory resistance Size M Artificial mechanics design, Reduce the burden on the neck Application to Spray painting/Pesticide spraying/Laboratory/Electroplating factory Anti-organic gas, hydrogen fluoride, hydrogen chloride, hydrogen sulfide, sulfur dioxide After normal wear smell of harmful smell please replace the filter cartridges The 3M Organic Vapor/Acid Gas Cartridge 6003 helps provide respiratory protection against certain organic vapors or acid gases,

### EMERGENCY ESCAPE BREATHING APPARATUS (EEBD)

- EEBD (Emergency Evacuation Breathing Device) is a device that is used to evacuate with safety, a dangerous enviroment that lacks normal breathing conditions caused by smoke from fire, gas leaks etc.
- The Lalizas Emergency Escape Breathing Device (EEBD), complies with the amended SOLAS.
- Flame resistant materials, silver in colour to reflect heat and be highly visible
- Durable and reliable construction with low maintenance
- Easy visual access on the pressure gauge
- With cylinder, hood and carrying bag



Brand: 3M Model: 6800+6003

Application	Spray painting/Pesticide spraying/Laboratory/Electroplating factory
Material	Silica gel/Polycarbonate lens
Gross Weight	800g
Certification	US NIOSH/ CN LA



**Brand:** Lalizas, made in Greece **Duration:** 10-15 mins.



# SELF-CONTAINED BREATHING APPARATUS (SCBA)

- Honeywell T8000 is a Self Contained Breathing Apparatus (SCBA) that is designed to provide a superior and effective safety product for respiratory protection in firefighting and industrial usage that complies with the EN137, Type II Classification.
- The T8000 SCBA from Honeywell understands a Firefighter's ensemble in high heat conditions, and the level of thermal performance.
- Firefighters need the finest protection against unforeseen circumstances that are immediately dangerous to life or health.
- Total Weight of the complete apparatus with charge cylinder: Approximately 11 kg
- High-pressure pneumatic gauge: 0-400 bar, photo-luminescent gauge, rubber protection and integrated alarm whistle
- Alarm activation: 55±5 bar
- Alarm volume: >90 dBA
- Approve temperatures:  $-30 \degree C 60 \degree C$
- Apparatus type-approvals: EN 137:2006 Type 2
- Full-face mask type-approval: EN 136 Class III
- Cylinder is made of carbon fiber
- Duration: 45mins

## FIRE BUCKET

- Manufactured from heavy duty stainless steel
- Ideal for use as a water or sand bucket.
- This handy little bucket with handle can be used to store the necessities to quickly put out a fire either indoors or outdoors.

### FIRE BLANKET

- Compact with good draping qualities.
- Designed to prevent Oxygen from reaching the burning Oil thereby extinguishing it.
- Ideal for landlords to fit in rented accomodation, kitchens etc. The Fire Blankets plastic container is designed to simply hang on a single screw or nail adjacent to the Hob or Cooker
- Alternative use: Made of Fire resistant materials they are useful for smothering Fat Pan fires or for wrapping around a person whos clothes are on Fire
- Fire Blankets should be kept near, not too close, to the Cooker in the Kitchen. Contact the Fire Brigade should the Fire get out of Hand.
- Size Available: 1..0m x 1.0m/ 1.8m x 1.8m





**Brand:** Honeywell, made in USA **Model:** EN T8000





### WORKSAFE LED FLASHLIGHT 80LUMENS

- The WorkSAFE LED series was developed using a proven product platform and integrating the highest LED technology. The LED technology significantly increased light output and run-time.
- INTRINSICALLY SAFE: The intrinsically safe certification on these lights gives you the absolute confidence to use our lights in the most hazardous environments w/o concern of any safety issues.
- For use in hazardous atmospheres
- 'S' Biner included for quick attachment
- Waterproof, IP67 rating
- 'Switch Guard' Prevents accidental lighting
- Three-way switch : On-Momentary-Off
- Anti-roll tube
- Faceted reflector for more light
- Safety Approvals
- UL Protection Methods
- Intrinsically Safe
- Divisions 1 & 2
- Class I, II, III Div 1 Groups A-G
- Class I, II, III Div 2 Groups A-G
- Operating Temp T5
- Specifications:
- Power Source: 2x 'D' Cell Alkaline
- Light Source: LED
- Life: 30,000 hrs
- Runtime: 200 hrs
- Light Output: 80 Lumens
- Beam Distance: 100 Meters
- Weight (Without batteries): 5.0 oz (.13 kg)
- Waterproof: 1 meter

### WORKSAFE LED FLASHLIGHT 60LUMENS

- For use in hazardous atmospheres
- 'S' Biner included for quick attachment
- Waterproof, IP 67 rating
- 'Switch Guard' prevents accidental lighting
- Anti-roll tube and Faceted reflector for more light
- Three way switch: On-Momentary-Of
- Specifications
- Power Source: 3 x 'D' Cell Alkaline
- Light Source: LED
- Life: 30,000 hrs
- Runtime: 250 hrs
- Beam Distance: 88 meters
- Light Output:60 Lumens
- Weight (Without batteries): 6.0 oz (.17 kg)
- Safety Approvals
- UL Protection Methods
- Intrinsically Safe
- Divisions 1 & 2
- Class I, II, III Div 1 Groups A-G
- Class I, II, III Div 2 Groups A-G
- Operating Temp T5
- Waterproof: 1 meter



**Brand:** Brightstar, made in USA **Model:** 2217



**Brand:** Brightstar, made in USA **Model:** 2224



GROUND FIRE HYDRANT	_
<ul> <li>The Chang Der common type ground fire hydrant has a 3" or 4" flanged inlet and 2 x 2 1/2 " machine / NST male outlet which permits the connection of fire hose to augment fire fighting water supply.</li> <li>Outlets are covered by matching cap and chain.</li> <li>The nydrant body is made of ductile cast iren and finished with anamel red paint.</li> <li>It can accommodate working pressures up to 10 Kgf/ cm<sup>2</sup> and test pressure u to 15 kgf / cm<sup>2</sup>.</li> </ul>	
	<b>Brand:</b> Chang Der <b>Model:</b> AVH 682 K = 3" <b>Model:</b> AVH 682 F = 4"
DRY CHEMICAL FIRE EXTINGUISHER	
<ul> <li>Dry chemical is highly recommended for all classes of fires A.B.C. powder type w/ non – toxic</li> <li>non – conducting and non – corrosive chemicals</li> <li>Fire extinguisher RED CYLINDER</li> <li>ISO Certified</li> <li>Quality Brand</li> <li>Available: 11b., 31bs., 5 lbs., 10 lbs. 20 lbs., 50 lbs.</li> </ul>	Brand: Cyclone
HCFC 123 FIRE EXTINGUISHER	
<ul> <li>HCFC-123 chemical fire extinguisher</li> <li>Clean Agent</li> <li>Chemical 2a2bc</li> <li>ISO Certified</li> <li>Quality Brand</li> <li>Available: 11b., 31bs., 5 lbs., 10 lbs. 20 lbs., 50 lbs.</li> </ul>	
	Brand: Cyclone
FIRE HOSE CABINET SURFACE MOUNTED (SET)	
<ul> <li>Stainless steel body G18 slanting roof. All steel w/ stainless hinge with hose rack</li> <li>Clear glass used for frontage</li> </ul>	
<ul> <li>With the following accessories:</li> <li>1<sup>1</sup>/<sub>2</sub> angle valve</li> <li>1<sup>1</sup>/<sub>2</sub> brass straight adjustable nozzle</li> <li>1<sup>1</sup>/<sub>2</sub> brass nipple</li> <li>10lbs. Fire Extinguisher Dry chemical</li> <li>Hose Rack</li> <li>Fire hose 1<sup>1</sup>/<sub>2</sub> x 100 feet single jacket with male</li> </ul>	
<ul> <li>and female couplings</li> <li>Fire hose cabinet dimension (inches): 32 x 27 x 7</li> </ul>	