

OTHER PULLEY

MOBILE PULLEY

- Compact and extremely lightweight, the MOBILE pulley is designed for a variety of uses.
- Ultra compact, lightweight pulley
- Designed for hauling systems and deviations
- Sheave mounted on self-lubricating bushings for good efficiency

Specifications

- Rope compatibility: 7 to 13 mm
- Sheave diameter: 21 mm
- Ball bearings: no
- Efficiency: 71 %
- Maximum working load: 2,5 kN x 2 = 5 kN
- Weight: 75 g
- Certification(s): CE EN 12278

FIXE PULLEY

- Ursatile and compact, the FIXE pulley allows quick installation onto the rope.
- Fixed side plates allow quick installation and coupling with a rope clamp
- Designed for hauling systems and deviations
- Sheave mounted on self-lubricating bushings for good efficiency
- **G** For use with OK or WILLIAM type carabiner

Specifications

- Rope compatibility: 7 to 13 mm
- Sheave diameter: 21 mm
- Ball bearings: no
- Efficiency: 71 %
- Maximum working load: 2,5 kN x 2 = 5 kN
- Weight: 90 g
- Certification(s): CE EN 12278

KNOT PASSING PULLEY

- High clearance rope channel allows passage of joining knots (long raise or Tyrolean traverse on two ropes)
- Large diameter sheave mounted on sealed ball bearings for excellent efficiency
- Locking pins on the sheave allow pulley to be used as an anchor

Specifications

- Rope compatibility: 8 to 19 mm
- Sheave diameter: 76 mm
- Ball bearings: yes
- Maximum working load: 5 kN x 2 = 10 kN
- Weight: 1390 g
- Height: 26 cm
- Certification(s): CE EN 12278



Brand: Petzl, made in France **Model:** Mobile



Brand: Petzl, made in France **Model:** Fixe



Brand: Petzl, made in France **Model:** Kootenay