



KERNMANTLE DYNAMIC ROPE

PETZL, made in France



- The 10.1 mm diameter MAMBO dynamic rope is designed for work at height professionals that use climbing techniques for progression.
- Dynamic rope limits the impact transmitted to the user in case of a fall
- Thick sheath improves abrasion resistance
- Certification (s): CE EN 892

Diameter	10.1mm
Model	Mambo
Material (s)	Nylon
Weight per meter	65 g
Impact force (factor 0.3)	8,5 kN
Number of factor 1,77 falls	7
Construction	42 carrier
Percentage of sheath	37%
Static elongation	8,5%
Dynamic elongation	34%

COUSIN, made in France



- Not only it is supple, but the Gran Torino 10.4 features an interesting value for the number of falls. It is ideal for intensive use, with remarkable durability.
- Advantages: Exceptional lifespan.
- Use: The reference rope for indoor use or intensive use.
- Certification (s): CE EN 892

Diameter	10.4 mm
Weight	71 g/m
Sheath percentage	41 %
Number of falls	7
Impact force	940 daN
Number of strands	32
Dynamic elongation	34.7 %
Static elongation	8.2%
Knotability	0.94
Breaking strength	2,215 daN
Component	100% polyamide high tenacity

TENDON, made in Czech Republic



- An excellent all-rounder and a good choice for those who want to possess one rope only. With extraordinary durability and great technical performance make the rope suitable for all kinds of climbing activities.
- This rope able to absorb a great impact force which would otherwise act on the climber's body during the fall.

Diameter	10.5mm
Sheath slippage	0 %
CE 1019	Yes
Number of UIAA falls min.	9
Number of UIAA falls max.	10
Max. impact force (kN)	7.9
Static elongation	6 %
Dynamic elongation	34 %
Knotability	0.8
EN 892	Yes
Weight (g/m)	69
UIAA	Yes